

Ultrasonic เครื่องทดสอบความแข็งระบบอัลตราโซนิค hardness tester



Made in
KOREA

SU-100

Specifications ▼

Model:	SU-100
Part Number:	882-121
Optional Probes:	Standard Probe: 2Kgf (Optional: 1Kgf, 5Kgf, 10Kgf)
Measuring Range:	HV: 50-999; HRC: 20-70; HB: 85-650
Accuracy:	HV: $\pm 3\%$ HV; HRC: ± 1.5 HRC; HB: $\pm 3\%$ HB; HLD: $\pm 3\%$ HLD
Measuring Direction:	Supports 360°
Data Storage:	Saves 1000 groups of measuring data and 20 groups of calibration data
Hardness Scale:	HV, HB, HRC
Data Display:	Loading force, testing times, testing results, average, maximum, deviation and conversion scale
Hardness Indication:	LCD display
Operating Temperature:	14°F - 122°F / -10°C - 50°C; Humidity: 30 - 80% R.H
Operating Voltage:	6V
Charger Voltage:	AC 110 / 60 Hz, 220V / 50 Hz
Dimensions:	6.3" x 3.15" x 1.2" / 160 x 80 x 31 mm
Weight:	1.1 lbs. / 0.5 kg

*สอบถามราคาได้ที่ 02-9744354-6 หรือสายด่วน 082-1288881, 081-7731860

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.
(Monday- Friday 8.30-17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com