

Ultrasonic Thickness Gauge

เครื่องวัดความหนาแบบ อัลตราโซนิก

MODEL CM8812 C ULTRASONIC THICKNESS GAUGE

Application : Used for measuring thickness and corrosion thickness of pressure vessels, chemical equipments, boilers, oil storage tanks, etc.



CM-8812 C



SPECIFICATION

Measuring range	1.2 – 200 mm/ 0.05 – 8 in for steel
Operating Principle	Ultrasonic
Test Material	Hard material such as steel, cast iron, aluminum, copper, brass, zinc, quartz glass, polyethylene, PVC, etc.
Sound velocity	1000 – 9000 m/s (3281 – 32806ft/s)
Resolution	0.1mm /0.001 in
Accuracy	+– (0.5% L+0.1) L is the measuring thickness in mm
Output	RS232C
Power supply	4 x 1.5 V AAA batteries
Working Condition	temperature 0 C (32 F – 122 F) Humidity <80% RH
Dimension	120 x 62 x 30mm
Weight	164g/5.80z

*สอบถามราคาได้ที่ 02-9744354-6 หรือสายด่วน 082-1288881, 081-7731860

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.

(Monday– Friday 8.30–17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com