

Potable hardness tester

เครื่องทดสอบความแข็งพกพา

IREI-100

Features

- Seven impact devices are available for speci application. Automatically identify the type of impact devices
- Large capacity memory could store 500 group (Relative to average times 321) information including single measured value, mean value, testing data, impact direction, impact times, material and hardness scale, etc.
- Upper and lower limit can be preset. It will alarm automatically when the result value exceeding the limit
- Battery information indicates the rest capacity of the battery and the charge status
- User calibration function
- USB port with the PC humanity multi-fuctions data proceeding software
- Original imported high speed thermal printer support the immediate printing function. It can save sata permanently
- NI-MH rechargeable battery as the power source charge circuit integrated inside the instrument. Continuous working period of no less than 150 hours (EL off and no printing)
- Auto power off to save energy
- Excellent after-sale service system for high quality products--two years' guarantee and all maintenance. Easy to buy and comfortable to use



Specifications

Type of	Hardness value of Leeb standard hardness block	Error of displayed	Repeatability
D	760 30HLD	6HLD	6HLD
	530 40HLD	10HLD	10HLD
DC	760 30HLDC	6HLDC	6HLD
	530 40HLDC	10HLDC	10HLD
DL	878 30HLDL	12HLDL	12HLDL
	736 40HLDL		
D+15	766 30HLD 15	12HLDL+15	12HLD+15
	544 40HLD 15		
G	590 40HLD	12HLG	12HLG
	500 40HLG		
E	725 30HLE	12HLE	12HLE
	508 40HLE		
C	822 30HLC	12HLC	12HLC
	590 40HLC		

*สอบถามราคาได้ที่ 02-9744354-6 หรือสายด่วน 082-1288881, 081-7731860

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.

(Monday- Friday 8.30-17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com