

Potable hardness tester

เครื่องทดสอบความแข็งพกพา

HL-200

Features

- Compact metal case, suitable for use under poor working conditions. Test at any angle, even upside down
- Wide measuring range. It can measure the hardness of all metallic materials. Direct display of hardness scales HRB, HRC, HV, HB, HS, HL
- Large screen (128x64 dot matrix LCD), showing all functions and parameters, With EL background light
- Large capacity memory could store 500 groups information
- Datapro software to connect with PC via USB port
- Software calibration function
- Outline : 132x76.2mm
- Weight : 345g



Specifications

Impact Device	Hardness value of Leeb/ Standard hardness block	Error of displayed value	Repeatability of displayed value
D	760±30HLD	±6 HLD	6HLD
	530±40HLD	±10 HLD	10HLD
DC	760±30HLD	±6 HLDC	6HLD
	530±40HLD	±10 HLDC	10HLD
DL	878±30HLD	±12 HLDL	12HLDL
	736±40HLD		
D+15	766±30HLD	±12 HLD+15	12HLD+15
	544±40HLD		
G	590±40HLD	±12 HLG	12HLG
	500±40HLD		
E	725±30HLD	±12 HLE	12HLE
	508±40HLD		
C	822±30HLD	±12 HLC	12HLC

*สอบถามราคาได้ที่ 02-9744354-6 หรือสายด่วน 082-1288881, 081-7731860

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.
(Monday- Friday 8.30-17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com