

Coating Thickness Gauge เครื่องวัดความหนาสี

เครื่องวัดความหนาสีรุ่นนี้ (เครื่องวัดความหนาสี ได้ทั้งโลหะ และอโลหะ)
เหล็ก สังกะสี อลูมิเนียมม ซิงค์ สแตนเลส ทองแดง
เป็นรุ่นใหม่ที่มีความสามารถสูง เครื่องวัดความหนาสีรุ่นนี้ สามารถ
Memory ได้ในตัว ถึง 99ค่า ตัวสาย และโพรบ มีความแข็งแรงสูง
สามารถวัดความหนาสี ได้ 0-250nm และสามารถ ตั้งค่า Max, Min
และ Alarm เตือนได้ ถือว่าเป็นรุ่นที่ สุดยอดครับ มีความแม่นยำสูง

CM-8856

SPECIFICATIONS

Feature

It meets the standards of both ISO2178 and ISO 2361 as well as DIN, ASTM and BS. It can be used both in the laboratory and in harsh field conditions. The F probes measure the thickness of non-magnetic materials (e.g. paint, plastic, porcelain enamel, copper, zinc, aluminum, chrome, etc.) on magnetic materials (e.g. iron, nickel, etc.) often used to measure the thickness of galvanizing layer, lacquer layer, porcelain enamel layer, phosphide layer, copper tile, aluminum tile, some alloy tile, paper, etc.

- Display : 4 digits LCD, backlit
- Range : 0 ~1250 um/0~50mil (other range can be specified)
- Min. radius workpiece
- F : Convex 1.5mm/ Concave 25mm
- N : Convex 3mm/ Concave 50mm
- Min. measuring area : 6mm
- Min. Sample thickness : 0.3mm
- Resolution : 0.1um (0 ~99.9um)
- 1um (over 100um)
- Accuracy : $\pm 1 \sim 3\%$ or 2.5um or 0.1mil (whichever is the greater)
- Battery indicator : Low batter indicator
- PC interface : with RS-232C interface
- Power supply : 2x1.5 AAA (UM-4) battery
- Operating condition : Temperature 0~50 °C
- Humidity : <95%
- Size : 126x65x35mm (5.0x2.6x1.6 inch)
- Weight : about 81g (not including batteries)



*สอบถามราคาได้ที่ 02-9744354-6 หรือสายด่วน 082-1288881, 081-7731860

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.
(Monday- Friday 8.30-17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com