

ITOKIN TECHNOLOGY

02-9744354-6

 www.itokin2000.com

 [channel/itokin2000.com](https://www.youtube.com/channel/itokin2000)

 [itokintechnology](https://www.facebook.com/itokintechnology)



Vibration Meter

TV-200&TV-260



MODEL	TV200	TV260
Parameter	RMS of vibration velocity (mm/s)	Acceleration, Velocity, Displacement
Testing range	Velocity: 0.1mm/s~ 199.9mm/s	Acceleration:0.1m/s ²
		Velocity: 0.1mm/s-199.9 mm/s(RMS)
		Displacement: 0.001mm-1.999 mm (peak-peak)
Accuracy	±5% ± 2digits	
Display	3 1/2 digits LCD	
Power supply	two button batteries(LR44 or SR44)	
Battery capacity	Approx. 5 hours working continuously	
Operating temperature	0°C ~ 40°C	
Humidity	<85%	
Dimension	150mm×22mm×16mm	

Features

Used for fast failure detecting of motor, electric fan, pump, air compressor, machine tools and so on
Compact size, small Weight, easy handling
Prompt testing of vibration on the workshop machines
For quick checking of unbalance misalignment, bearings and gears

Guard against mechanical malfunction
Holding tested value for 40 seconds
Automatic switch off after 40 seconds

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.

(Monday- Friday 8.30-17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com