

02-9744354-6

www.itokin2000.com

channal/itokin2000.com

itokintechnology

Profile Projector

SP-3025



This series of profile projectors are famous for its excellent quality of the optical system. It is processed of clear image and accurate magnification. The error of the contour measuring is less than 0.08% under the illumination of transmission. This instrument provides the mini-printer (option) and foot-switch, which are convenient to output and gather the data. You can adjust the focus by ascending and descending the projection box.

The measuring and profile projector is with big travel and stationary performance because the working table does not ascend or descend. The instrument can also measure the big range with high precision.

MODEL	REVERSE IMAGE	SP-3025
Working table	The metal table's size	450x280
	The glass table's size	306x196
	X-axis travel(mm)	250
	Y-axis travel(mm)	100
	Z-axis travel(mm)	100 (for focus)
	Measuring accuracy(um)	3+L/75
	Resolution (X-axis, Y-axis)	0.5um
Projector screen	Screen size(mm)	ø312 used range> ø300 (with the meter line)
	Screen rotary range	0°~ 360°
	Resolution (X-axis, Y-axis)	1' or 0.01°
Lens	Magnification	10X(option)
	Object view (mm)	ø30
	Working distance(mm)	77.7
	Max. workpiece height	90mm
DRO	DC-3000 multi-function DRO	
Illumination	The illumination of transmission and reflection : 24V/150W-halogen lamp	
Power	110V/220VZAC), 50/60Hz, Total power=400W	
Dimension	LxWxH(mm)	780x780x1100
weight	Unit : (Kg)	180
Optional	Mini-printer (optional), Edge detector (optional), software (optional)	

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.
(Monday- Friday 8.30-17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com

WWW.ITOKIN2000.COM