

Ultrasonic Thickness Gauge

เครื่องวัดความหนาแบบ อัลตราโซนิก

Measuring Range in Steel
0.040 – 8.00 inches
1.00 – 200.0 mm

TI-45NA Ultrasonic Wall Thickness Gauge accurately measures wall thickness and the extent of corrosion of all metals, ceramics, glass and most rigid plastics – from only one side! The attractive, ergonomic housing design is extremely compact, lightweight and rugged. It fits comfortably in the palm of your hand and incorporates a back light that illuminates the LCD in poorly lit areas.



IT-45N

ULTRASONIC THICKNESS

Features

- TI-45NA includes new Pipe Mode for stable measurement on small diameter pipe (1" and larger)
- Resolution of 0.001" (0.01mm)
- Extremely small & lightweight operates from a single AA battery
- Switch-selectable units – inches or mm
- Built-in calibration test plate
- Quick display update with last reading retained on the display
- Display symbols alert user to poor coupling and low battery conditions
- TI-45N-HD includes slip-on, ergonomic rubber sleeve for improved grip and additional physical protection
- User Adjustment of Acoustic Velocity or selection 10 preset velocities

*สอบถามราคาได้ที่ 02-9744354-6 หรือสายด่วน 082-1288881, 081-7731860

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.
(Monday- Friday 8.30-17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com