

Coating Thickness Gauge เครื่องวัดความหนาสี

เครื่องวัดความหนาสีรุ่นนี้ เป็นรุ่นที่สามารถวัดความหนาสีบนไม้ บนปูน บนพลาสติก โดยใช้หลักการ Ultrasonic ในการวัดสามารถบันทึกข้อมูลได้ เป็นผลิตภัณฑ์จากสหรัฐอเมริกา พร้อม Calibration Certificate จาก NIST

*ติดต่อสอบถามได้ที่ 02-9744354-6 หรือสายด่วน
082-1288881, 081-7731860

PT-200

Specification List

Features

- USB/ Serial/ IR ports for downloading to a PC, printer or data collector
- Solvent, acid, oil, water and dust resistant meets or exceeds IP5X
- Scratch and solvent resistant lens
- Thick impact-resistant lexan display
- Bi-color indicator light
- Shock-absorbing, protective rubber holster
- Quality high-flex cable and strain relief
- Comfortable ergonomic finger grip reduce operator fatigue
- Plastic-tipped probe will not scratch surface



PosiTector 200	B/Std	B/Adv	C/Std	C/Adv
Measure total thickness	Yes	Yes	Yes	Yes
Measure individual layers		Yes		Yes
Graphic display		Yes		Yes
Typical applications	Polymer coatings		Thicker coating	
	on wood, plastic, etc,		on concrete, fiberglass, etc.	
Range	13-1000 microns		50-3800 microns	
	0.5-40 mils		2-150mils	
Accuracy	±(2 microns + 3% of reading)			
	±(0.1 mils + 3% of reading)			
Minimum individual		13 microns		50 microns
layer thickness		0.5 mils		2 mils
Calibration standard	DeFelsko CAL-A4		DeFelsko CAL-P6	

*สอบถามราคาได้ที่ 02-9744354-6 หรือสายด่วน 082-1288881, 081-7731860

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.
(Monday- Friday 8.30-17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com