

Ultrasonic Thickness Gauge

เครื่องวัดความหนาแบบ อัลตราโซนิก

Features

- Automatic Self Calibration
- Couplant Indicator
- Automatic Power Off Device
- High - Low Limit Alarm
- LCD Brightness Adjust
- Through Coating Capability
- Low Battery Indicator

Velocity Range	1000 - 9999 m/s (0.0393 - 0.3936 inch/us)
Display Type	4 Digital LCD with advanced backlight
Memory	500 Test Values
Power	2 pcs. 1.5v AA Batteries
Outside Dimension	149 mm x 73 mm x 32 mm
Weight	160 g

TM-230D
TM-250D



Through Paint or Coating Ultrasonic Thickness Gauge

SPECIFICATION

Specification		TM-230D	TM-250D
Measuring Range (Steel)	Standard	0.8 mm - 250 mm Depending of the Probes	
	Through Coating	3 mm - 18 mm Depnding of the probes	
Display Resolution		0.1 mm or 0.01 inch	0.1 mm / 0.1 mm or 0.01 inch /0.01 inch
Tolerance		+ - 0.1 mm in steel	+ - 0.025 mm in steel

*สอบถามราคาได้ที่ 02-9744354-6 หรือสายด่วน 082-1288881, 081-7731860

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.
(Monday- Friday 8.30-17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com