

Potable hardness tester

เครื่องทดสอบความแข็ง พกพา



THL-280

Specifications

Hardness Scale	HL, HB, HRB, HRC, HRA, HV, HS
Memory	48 - 600 Groups (impact Times : 32 - 1)
Measuring Range	HLD(170 - 960) See below table 1 and table 2
Accuracy	+/- HLD (760 +/- 30 HLD) Error of Displayed Value 4HLD (760 +/- 30 HLD) Repeatability of Displayed Value
Standard Impact Device	D
Optional Impact Devices	DC/D + 15 /G/C/DL
Max. Workpiece Hardness	996 HV (For Impact Devices D/DC/DL/D+15/C) 646 HB (For Impact Device G)
Min. Radius of Workpiece	Rmin = 50 mm (with special support ring Rmin = 10 mm)
Min. Workpiece Weight	2 - 5 Kg on Stable Support 0.05 - 2 Kg with Compact Coupling
Min. Workpiece Thickness	5 mm (impact Devices D/DC/DL/D+15) 1 mm (impact Device C) 10 mm (impact Device G)
Min. Thickness of Hardened	0.8 mm
Power	AA Battery
Continuous Working Time	approx. 100 h (no back light off)
Charging Time	2 - 3.5 h
Operating Temperature	0 -40
Relative Humidity	< 90%
Overall Dimensions	125 x 67 x 31 mm (main unit)
Weight	0.3 Kg (main Unit)

*สอบถามราคาได้ที่ 02-9744354-6 หรือสายด่วน 082-1288881, 081-7731860

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.
(Monday- Friday 8.30-17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com