

Potable hardness tester

เครื่องทดสอบความแข็งพกพา

HM6561

Features

- Die cavity of molds
- Inspection of bearing and other mass produced parts on a production line
- Failure analysis of pressure vessel, steam generator and other equipment
- Inspection of installed machinery, permanent parts of assembled systems and heavy work pieces.
- Testing surface of a small hollow space
- Material identification in the warehouse of metallic materials
- Rapid testing in large range and multi-measuring areas for large-scale work piece



Specifications

Display	12.5mm LCD with back light
Accuracy	Display error $\pm 0.8\%$ at LD=900
Measuring range	200-900L
Conversion	HL-HRC-HRB-HB-HV-HSD
Materials	9 different common materials
	With RS232C interface
Memory	250 data can be stored and re-readable
Impact device	D Will handle the majority of hardness testing
Power supply	2x1.5V AAA size battery
Dimension	146 x 65 x 36mm
Weight	130g (not including batteries)
Working temperature	-10°C ~ +50°C
Storage temperature	-30°C ~ +60°C;
Relative humidity	$\leq 90\%$
Applications. Weight	75g

*สอบถามราคาได้ที่ 02-9744354-6 หรือสายด่วน 082-1288881, 081-7731860

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.
(Monday- Friday 8.30-17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com