

STANDARD COLOUR BOX

ตู้เทียบสี

www.itokin2000.com



MODEL

SP-60 (4 Lights)

SP-65 (5 Lights)

SP-66 (6 Lights)

SP-120 (6 Lights)

Features:

Microcomputer controlled.

Quick and reliable Color assessment;

Auto conversion between light sources;

No warm-up; No flick; No heat emission;

Elapsed Time displaying of each light source.

Energy saving; Efficient illumination.

Light Instruction

D65-International standard artificial daylight;

UV-Ultraviolet light source;

F-Fluorescent;

TL83-/U30-American commercial light source.

TL84 West European and Japanese store light source;

CWF-Cool white fluorescent, American store light source;

Other light sources, such as A light, D50 light etc are available.

All the light sources fittings are original imported from international famous brand.

Model	Equipped with	Size (CM)
SP - 60 (4Lights)	Equipped with D65X2, TL84X2, UVX1, FX4	71 W x 40.5 D x 57 H
	4 Kind Lights	Cavity : 68 W x 38 D x 36 H
SP - 65 (5Lights)	Equipped with D65X2, TL84X2, CWF2, UVX1, FX4	71 W x 40.5 D x 57 H
	5 Kind Lights	Cavity : 68 W x 38 D x 36 H
SP - 66 (6Lights)	Equipped with D65X2, TL84X2, CWF2, TL83X2, UVX1, FX4	71 W x 53 D x 58 H
	6 Kind Lights	Cavity : 68 W x 51 D x 41 H
SP - 120	D65X2, TL84X2, CWF2, TL83X2, UVX1, FX6	131 W x 61 D x 80 H
	6 Kind Lights	Cavity : 128 W x 59 D x 60 H

ISO DIN BSI ANSI CIE, ASTM D1729, SAE J361, Tappi 7515, BS-950 Part 2 and AS 1580. 6001. 1 etc.



www.itokin2000.com



itokintechnology.co.,LTD



Tel : 02-9744354-6

