

Ultrasonic เครื่องทดสอบความแข็งระบบอัลตราโซนิก hardness tester



SH-21

Specifications ▼

Measuring Indenter	Diamond indenter for Micro-Vickers (facing-to-surface angle of 136 deg)
Measuring load	Approx 1kgf (roughly 10N) Approx 2kgf (roughly 20N) (These loads indicate those in typical applications. As the specification varies according to the object to be measured, please contact us for details.)
Measuring range	Rockwell hardness: 10.0 HRC to 70.0 HRC Vickers hardness: 100 HV to 999 HV Shore hardness: 20.0 HS to 99.9 HS Brinell hardness: 85 HBW to 550 HBW
Reproducibility	HRC: ± 1.0 HRC , HV : $\pm (3\%rdg)$ HV , HS: ± 1.0 HS , HBW : $\pm (3\%rdg)$ HBW
Power source	AC adapter (100 to 240V) or lithium ion rechargeable battery
Minimum target size	15 mm (width) x 15 mm (length) x 7 mm (thickness)

*สอบถามราคาได้ที่ 02-9744354-6 หรือสายด่วน 082-1288881, 081-7731860

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33,Vibhavadi Rangsit Road, 1-6 Separate.Airport, Don Muang, Bangkok 10210 Thailand.
(Monday- Friday 8.30-17.30) E-mail:salesitokin@gmail.com /www.itokin2000.com