

Salt Spray Tester

Model SPQ

Feature:

This tester is used for the surface erosion resistance test of kinds of material processed by paint, plating, anodized

Standard:

GB/T5170.8, GB/T2423.17, ISO-3768 3769
3770, ASTM-B117 B268, JIS-D0201 H8502 H8610 K5400
Z2371

Application:

1. Watered by itself while lack of water.
2. Precise spray can work 2000 hours without crystallized jam.
3. Made of Japanese PVC, environmental protection and high anti-aging capability, spray is made of transparent PVC.
4. SSR: precisely digital thermal controller with spray protection system.



02-9744354-6

www.itokin2000.com

[channel/itokin2000.com](https://www.youtube.com/channel/itokin2000.com)

[itokintechnology](https://www.facebook.com/itokintechnology)

Specifications

| Model | SPQ-150 | SPQ-250 | SPQ-750 | SPQ-1000 |
|----------------------|----------------------------------|----------------------|-----------------------|-----------------------|
| Test Room (WxLxH) | 600 x 450 x 400 mm | 900 x 600 x 450 mm | 1200 x 850 x 500 mm | 1600 x 1000 x 600 mm |
| Lite | 108 ml | 243 ml | 510 ml | 960 ml |
| Machine Size (WxLxH) | 1130 x 630 x 1070 mm | 1460 x 910 x 1280 mm | 2200 x 1200 x 1450 mm | 2600 x 1450 x 1600 mm |
| Lab temperature | NSS.ACSS 35°C 1 °C/CASS 50°C 1°C | | | |
| Humidity | 85% ~ 98% RH | | | |
| Temperature range | ± 0.5 °C | | | |
| Salt Spray Subside | 1.0~2.0 ml/ 80 cm 2/h | | | |
| Power Supply | AC220V 10A | AC220V 15A | AC220V 20A | AC220V 30A |

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33, Vibhavadi Rangsit Road, 1-6 Separate, Airport, Don Muang, Bangkok 10210 Thailand.

(Monday- Friday 8.30-17.30) E-mail: salesitokin@gmail.com /www.itokin2000.com