

Spectrophoto Meter เครื่องวัดเฉดสี

FEATURES

- Easy operation makes you use it easily.
- Widely applied to quality control of plastic and printing industries.
- Display directly color difference by E^*ab , L^*a^*b , $CIE_{L^*a^*b}$, $CIE_{L^*c^*h}$.
- Standard deviation within E^*ab 0.2 (test condition: choose average values by 12 pcs white tabula).
- It can be connected with computer to do the inspection by software with USB expansion interface.



SC-20

Specification List

Model Spectrophotometer SC 20

Accuracy $<0.2 \Delta E^*ab$

Display ΔE^*ab , CIE_{Lab} , ΔLab , CIE_{Lch}

Test range L: 0~100, a: -128~127, b: -128~127

Test time About 3 seconds

Test interval 2 seconds

Aperture (mm) $\varnothing 8$

Power off Automatically in 5 min

Light source C light source

Dimension (mm) 77 x 86 x 210

Sensor Silicon photodiode array

Power Supply DC/5V (1.5A)/2 x 1.5V (AAA) battery

Working environment 0~40C, < 85%RH

Weight (g) 204

Dimension (mm) 171 x 50 x 49

Application Measure any color of smooth surfaces



*สอบถามราคาได้ที่ 02-9744354-6 หรือสายด่วน 082-1288881, 081-7731860

ITOKIN TECHNOLOGY CO., LTD.

3/18 Soi 33, Vibhavadi Rangsit Road, 1-6 Separate, Airport, Don Muang, Bangkok 10210 Thailand.

(Monday- Friday 8.30-17.30) E-mail: salesitokin@gmail.com /www.itokin2000.com