

# Gloss Meter CS-300S



## Gloss Meter

### Advantages

- 2x3mm small aperture;
- Repeatability reaches 0.2GU;
- Free PC software to test and generate test report.
- 3000mAh battery for continuous measurement 50000 times.

## Aperture Gloss Meter

### Portable Small

## SPECIFICATION

|                       |                                                                              |
|-----------------------|------------------------------------------------------------------------------|
| Model                 | CS-300S                                                                      |
| Test Angle            | 60°                                                                          |
| Measurement Range     | 60°:0-600GU                                                                  |
| Reproducibility       | 0-100:0.1GU                                                                  |
|                       | ≥100: 1GU                                                                    |
| Test Mode             | Simple and Statistic Mode                                                    |
| Light Source Lifetime | 300 million; 10 years                                                        |
| Measurement Time      | Less than 1s                                                                 |
| Storage Memory        | 100 pcs target, 10000 pcs samples                                            |
| Instrument Size       | 165x51x77 mm                                                                 |
| Instrument Weight     | About 400g                                                                   |
| Language              | English and Chinese                                                          |
| Battery               | 3000mAh lithium battery                                                      |
| Interface             | USB, Bluetooth (option)                                                      |
| Working Temperature   | 0-40°C                                                                       |
| Standard Accessories  | 5V/1A charger, USB cable, operate manual, CD (PC software), calibration tile |

02-9744354-6