

Endo SCOPE

ITK-Q401D

3.9mm x 1.0M
industry
video endoscope



ITK-Q601D

5.5 mm



5.5mm x 1.0M
Wireless
video endoscope



salesitokin@gmail.com



www.itokin2000.com



02-9744354-6

Endo Scope

ITK-Q401D

3.9mm x 1.0M

industry video endoscope



Insertion Tube Specifications

Image Sensor CMOS Image Sensor

Resolution (Dynamic/Static)

320(H) X 240(V)

720(H)x525(V)(N) / 720(H)x625(V)(P)

712 (H)x480(V) (N) / 720(H)x576(V)(P)

Insertion Tube Tip Diameter : 3.9mm .

Frame Rate ~30 fps

Exposure Automatic

White Balance Fixed

Field-of View (FOV) : 70°

Depth-of-Field (DOF) : 10mm - 200 mm

System Magnification 8X at 15 mm

Light Source : 4 White LED

Working Temperature : (-20° to 70°C)

Material of Tube : Semi-rigid / Soft-metal

Extended Length : 1.0M

Waterproof Standard : IP67

DVM Specifications

Power DC : 5V

Display : 3.5" TFT LCD Monitor 320 x 240 Pixels



100%
true

Interface Mini : USB 2.0 / AV Out

Battery Rechargeable: Li-Polymer Battery (3.7V)

Video Output Format : NTSC & PAL

Recording Medium SD Card : (Capacity up to 32G)

Still Image Storage Format JPEG : (640 x 480)

Video Recording Storage Format : AVI (320 x 240)

Language English + option : (Nine language)

Working/Storage Temperature : (-20° to 60°C)

While Charging Battery Temperature: (0° to 40°C)



salesitokin@gmail.com



www.itokin2000.com



02-9744354-6

Endo Scope

ITK-Q601D

5.5mm x 1.0M

Wireless video endoscope

Insertion Tube Specifications

Image Sensor CMOS Image Sensor

Resolution (Dynamic/Static)

320(H) X 240(V)

720(H)x525(V)(N) / 720(H)x625(V)(P)

712 (H)x480(V) (N) / 720(H)x576(V)(P)

Insertion Tube Tip Diameter : 3.9mm .

Frame Rate ~30 fps

Exposure Automatic

White Balance Fixed

Field-of View (FOV) : 70°

Depth-of-Field (DOF) : 10mm - 200 mm

System Magnification 8X at 15 mm

Light Source : 4 White LED

Working Temperature : (-20° to 70°C)

Material of Tube : Semi-rigid / Soft-metal

Extended Length : 1.0M

Waterproof Standard : IP67

DVM Specifications

Power DC : 5V

Display : 3.5" TFT LCD Monitor 320 x 240 Pixels

5.5 mm



9.0mm Probes
4 LEDs
0.3MPixel

Semi-rigid snake tube
waterproof, IP67
PVC Coated
standard length 1m

4Pins
AV Singal

Interface Mini : USB 2.0 / AV Out

Battery Rechargeable: Li-Polymer Battery (3.7V)

Video Output Format : NTSC & PAL

Recording Medium SD Card : (Capacity up to 32G)

Still Image Storage Format JPEG : (640 x 480)

Video Recording Storage Format : AVI (320 x 240)

Language English + option : (Nine language)

Working/Storage Temperature : (-20° to 60°C)

While Charging Battery Temperature: (0° to 40°C)



salesitokin@gmail.com



www.itokin2000.com



02-9744354-6

Endo Scope

ITK-Q401D

ITK-Q601D



Carton



PE Box



salesitokin@gmail.com



www.itokin2000.com



02-9744354-6