

SALT SPRAY

TOUCHED SCREEN

LR-G007

LINE : @ITOKIN2000.COM
TEL : 02-9744354-6
EMAIL : SALESITOKIN@GMAIL.COM

Use:

This machine has a standardized test method to check corrosion resistance of coated samples. Salt spray test is an accelerated corrosion test that produces a corrosive attack to the coated samples in order to predict its suitability in use as a protective finish. The appearance of corrosion products (oxides) is evaluated after a period of time. Test duration depends on the corrosion resistance of the coating; the more corrosion resistant the coating is, the longer the period in testing without showing signs of corrosion. Different coatings have different behaviour in salt spray test and consequently, test duration will differ from one type of coating to another.

Design Standards :ISO 9227,GB/T 2423.17-1993 ,GB/T 2423.18-2000,GB/T 10125-1997,ASTM.B117-97

JIS H8502 ,IEC68-2-11,IEC68-2-52 1996 ,GB.10587-89,CNS.4158,CNS.4159,-CASS,GB/T 12967.3-91 CASS



Inner Chamber



Inner size:

600×450×400mm (W * D * H)

Outside size:1070*600*1180mm (W * D * H)

Power:220V 2KW 50HZ

Temperature ranges: RT + 10 ℃ ~ 55 ℃

Humidity range: ≥ 93%R.H

Temperature uniformity: ± 2 ℃

Temperature fluctuation degree: ± 0.5 ℃

Fog settlement: 1 ~ 2 ml / 80 c ℃

Spray mode: continuous/periodic optional

Controller

