



CHECKLINE®
MADE TO MEASURE

PRECISION QUALITY CONTROL INSTRUMENTS SINCE 1958

Features

Total Measuring Range *

0.025 - 36.000 in / 0.63 - 914.4mm

Measuring Range on Steel **

0.025 - 6.00 in / 0.60 - 150.0mm

- NIST-traceable Calibration Certificate
- Resolution of 0.001 inch (0.01mm)
- Switch-selected units (inches or mm)
- Hi/Low alarm limits visually indicate out of tolerance readings
- 2-point calibration optimizes linearity over a wide measurement range
- Scan mode (100 readings/sec.) displays minimum thickness during the "scan"
- 5-step GAIN adjustment for optimal accuracy in challenging applications
- The extruded aluminum housing is impact-resistant and environmentally sealed (IP 65) for trouble-free use under tough field conditions
- 10,000 data values stored in up to 40 batches with 250 values/batch with USB data output
- LCD Display shows thickness value, velocity setting, gain setting, stability & battery indicators, scan mode, zero, File/Data and units
- Two (2) AA batteries provide 45-hours of continuous operation
- Selectable Backlight ON/OFF/AUTO
- 5-year warranty, CE-certified and Made in USA

* Depends on material and transducer/probe type

** With standard T-102-3300 probe

TI-25DLX

Data Logging Wall Thickness Gauge with USB Output

Built-in datalogger for 10,000 values in up to 40 batches with USB output

The Check-Line® TI-25DLX Wall Thickness Gauge accurately measures wall thickness and the extent of corrosion of all metals, ceramics, glass and most rigid plastics—from only one side! It incorporates built-in datalogging for 10,000 values with 250 readings per batch, up to 40 separate batches with USB Output. Data can be transferred into any program in .csv format or viewed in Datacomm Software (free download).

The TI-25DLX permits the operator to select from 8 preset materials as well as program 2 custom material velocities, plus allows free adjustment of the velocity as desired and allows the end-user to calibrate to a sample of known thickness where the velocity is automatically calculated.

To optimize linearity over a wide range, the user can perform a two-point calibration to two samples of known thickness. The optimal velocity is calculated to provide the highest accuracy and linearity between the low and high calibration points. Calibration and setup parameters can be locked to prevent accidental adjustments.

The complete kit includes: TI-25DLX gauge, probe, 4 oz. bottle of coupling fluid, 2 AA batteries, USB-C data output cable, NIST-traceable calibration certificate and instruction manual—all in a foam-fitted carrying case.



CHECKLINE®
MADE TO MEASURE

Checkline • 600 Oakland Ave, Cedarhurst NY 11516 - USA
www.Checkline.com • info@checkline.com • 516-295-4300

Specifications

Total Measuring Range (Steel)	0.025 – 36.000" (0.63 – 914.4mm) depends on material and transducer/probe type	Display Backlight	Backlight is selectable on/off/auto, and selectable brightness (Lo, Med, Hi)
Measuring Range (Steel)	0.040 – 6.000" (1.00 – 150.0mm) with standard transducer T-102-3300	Display Update	10 Hz (10 updates/sec)
Resolution	0.001" (0.01mm)	Temp. Limits	<i>Ambient:</i> –22 to 167 °F (–30 to 75 °C) <i>Material:</i> 0 to 200 °F (–20 to 100 °C) High temperature probes available
Measuring Modes	Pulse-Echo (P-E), Differential	Battery Type	2x AA batteries (rechargeable batteries can be used)
Output Type	USB-C (plug-n-play, view files on PC which can be dragged and dropped)	Battery Life	45 hours continuous use
Built-In Memory	10,000 data values stored in up to 40 batches with 250 values/batch	Housing	Extruded aluminum body with nickel-plated aluminum end caps (gasket sealed)
Memory Type	Sequential data file (single column)	Housing Rating	IP65
Velocity Range	0.0120 to .7300 in/μs. 305 to 18,542 meters/sec	Keypad	Sealed membrane that is resistant to both water and petroleum products Seven or eight tactile-feedback keys
GAIN Adjustment	Adjustable GAIN 5-position (VLOW, LOW, MED, HIGH, VH), in 3dB steps, 40-52dB	Weight	11 oz. (308 grams)
Probe (Standard)	1/4", 5 MHz Dual Element Transducer, actual wearface is 5/8" (17mm), p/n T-102-2000	Pulse Repetition Frequency (PRF)	200 Hz (200 pulses/sec)
Cable	4 ft. (1.2 m) waterproof cable with non-polarized, quick-disconnect connectors	Dimensions	2.5" x 5.17" x 1.25" (63.5 x 131.3 x 31.5mm)
Probes (optional)	1 to 10 MHz, 3/16" up to 1 inch (custom probes available)	Accessories	Probe/cable assembly, 4 oz. bottle of coupling fluid, NIST Calibration Certificate, 2 AA batteries, operating instructions, hard-plastic carrying case.
Probe Wearface	PEEK (Polyethylethylkytone)	Certifications	NIST Traceable and MIL-STD-45662A
LCD Display	Multi-function 7 segment 4.5 digit liquid crystal display with 0.500" digit height. Two 0.125 in 14 segment fields for labels and values, and one 7 segment field for labels and values. Additional icons to indicate features and modes	Warranty	<i>Gauge:</i> 5 Years <i>Probes:</i> 90 Days



Measuring Limits

	Minimum Radius for Convex Surfaces	0.350" (8.89mm)
	Minimum Radius for Concave Surfaces	3" (76.2mm)
	Minimum Headroom	1" (25.0mm)
	Minimum Sample Diameter	0.150" (3.8mm)
	Minimum Substrate Thickness - F	na
	Minimum Substrate Thickness - NFe	na

Related Products

SB-Series Certified Steel Test Blocks	<ul style="list-style-type: none"> Precision Machined and Finished Includes Wooden Storage Box Includes NIST Traceable Calibration Certificate
TICC-M Protective Holder for Ultrasonic Gauges	<ul style="list-style-type: none"> Constructed from heavy-duty Cordura Nylon Built-in belt loop
V-Block Ultrasonic Transducer Holder	<ul style="list-style-type: none"> For 3/16" & 1/4" Transducers only
SB Step Block Steel Test Blocks without certification	<ul style="list-style-type: none"> Fabricated from 1018 Steel Supplied without certification
CF-12 Coupling Fluid	<ul style="list-style-type: none"> Temp Range: 0 - 200 °F, -18 - 93 °C
TI-25-UW-50 50 Ft. Underwater Probe / Cable Assembly	<ul style="list-style-type: none"> 50 Ft. Length, Waterproof Probe/Cable assembly with non-polarized, Dual-Lemo connectors.