

INSPECTION ARTICULATING ENDOSCOPY CAMERA **SZG401J**



SZG401J industrial endoscope camera owns a 3.5-inch LCD screen with 600,000 pixels that delivers the most realistic and clear color images and videos.



Memory card 32GB

3,5 inch LCD Screen




Tube System	Tube Length	1m	1.5m
	Tube Material	tungsten alloy	
	Camera Pixels	1 mega pixels	
	Image Resolution	1280*720	
	DOF	10-100mm	
	FOV	120°	
	Light Source	LED ceramic light	
	Illuminance	25000Lx	
	Protecting Device of Durability	80mm buffer protection device on the connection between tube and handle	
	Articulation	360° joystick-control articulation	
Monitor System	Bending Angle	maximum: 220°	
	Structure	hand-held integrated design	
	Display	3.5 inches IPS full-view display	
	Zoom In/Out	5X	
	Image Effect	image freezing, cold/warm color	
	Image Adjustment	image sharpness/ contrast/gamma value	
	Image/Video Format	JPEG/MP4	
	File Storage	standard TF card: 16G, Maximum: 64G	
	Data Port	HDMI video output, Micro USB port	
	Wireless Image Transmission	WIFI (optional)	
Accessories	Battery	detachable & rechargeable lithium battery	
	Battery Capacity	3.7V, 3200mAh	
	Battery Working Time	≥3H	
	Battery Charge	DC 5V/1A	
	Outer Case Material	anti-fall engineering alloy material	
	Water/Dust Proof	probe/tube: IP67; monitor: IP65	
	Weight	≈0.5KG	
	Standard Configuration	instrument case/ videoscope/ battery card reader/ TF card/charger/ USB cable/ manual	
	optional	extendable pole: 0.35-1.8m/mini HDMI cable/ foldable tripod	



The whole product is dust-proof and water-proof



excellent quality, anti-fall and wear-resistant



super long working time



optional accessories



LINE : @ITOKIN2000.COM
TEL : 02-9744354-6
EMAIL : SALESITOKIN@GMAIL.COM