



# MG6-SM

## Gloss Meter

Measuring Range 0 to 999 GU

Measuring Angle 60°

Accuracy 0 to 120 GU:  $\pm 2$  GU ; 121 to 999 GU:  $\pm 1.5\%$  GU

Resolution (Division Value) 1 GU

Repeatability

Measuring Area (mm) 20 x 10 mm

Display black and white screen

Backlit Display N/A

Auto Shut-off N/A

Low Battery Indicator Yes

Power Supply One AA battery

Internal Memory N/A

Remote Interface N/A

Certifications/ Meets Standards ASTM D2457, ASTM D523, GB/T13891, GB7706 and GB8807

Operation Temperature -10~40°C (-50~104°F)

Storage Temperature -10~60°C (-50~140°F)

Operating Humidity Range Up to 85% no moisture condensation, for operation

Dimensions 4.84 x 2.56 x 1.50" (123 x 65 x 38 mm)

Weight 300 g

Standard Accessories Holder with Calibrating Tile (Working Standard), Checking Tile (Spare Working Standard), AA-Size Alkaline Battery, User Manual, Inspection Certification, and Guarantee Card.

## Applications

- Metallic finishes
- Appliances
- Furniture
- Light fixtures



- Designed for metal and metallic finishes such as bronze, copper, brass, aluminum, stainless steel, nickel plating and chrome plating
- Universal 60° angle with 1000 GU range and 1 GU display increments
- Compact design with metallic-mirrored calibration tile for optimized measurements
- Easy to use, simple set up
- Operates on single AA battery
- Includes: Holder with Calibrating Tile (Working Standard), Checking Tile (Spare Working Standard), AA-Size Alkaline Battery, User Manual, Inspection Certification, and Guarantee Card.



LINE : @ITOKIN2000.COM  
TEL : 02-9744354-6  
EMAIL : SALES@ITOKIN@GMAIL.COM

