
## **M**<sup>†</sup>kr<del>o</del>s<sup>†</sup>ze<sup>®</sup>

## PORTABLE SURFACE ROUGHNESS TESTER CODE: iSurfa-100



make the instrument work for a long time, which is suitable for all kinds of field use.

•The sensor probe has a protective door, which effectively protects the sensor probe

and ensures the accuracy of measurement.



Battery Compartment

Probe



Calibration Block



Bluetooth Adapter




STANDARD	DELIVERY

Main Unit	1
Calibration Block	1
Operating Manual	1
Certificate	1
Guarantee Card	1
Suitcase	1
Screwdriver	1

**OPTIONAL DELIVERY Bluetooth Adapter** 





arameter(µm)	Ra,Rz,Rq,Rt
ravel Length(mm)	5.6
ample Length(mm)	0.25,0.80,2.50
valuation Length(mm)	1.25,4.0
isplay Error	±10%
isplay Variability	<12%
tylus Radius and Angle	90°(+5°,-10°)
tylus Radius	10μm±1 μm
leasuring Force of Probe	≤0.016N
orce Change Rate	≤800N/m
ensor Guide Pressure	≤0.5N
attery	One 1.5V AA dry battery
imensions	73mm×28mm×62mm
/eight	220g
Vorking Environment	Temperature: -20°C~40°C
onditions	Relative humidity: < 90%
	No vibration and corrosive medium around

software